
SAFETY DATA SHEET

IMTECH RUBBER PRODUCTS

STR-PVC

Section 1 – CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Products Name: STR-PVC
Chemical Family: Synthetic elastomers and organic solvents
Applications: Adhesive

Supplier's Name: **IMTECH Rubber Products**
1225 W. Main St.
Elko, NV 89801
Tel: (800) 738-0308 Fax: (877) 638-0308

Prepared by: IMTECH Rubber Products
Preparation Date of SDS: October 27, 2015
24 Hour Emergency Telephone Number (ChemTel): 800-255-3924 / +01-813-248-0585

Section 2 – HAZARD(S) IDENTIFICATION

WHMIS Hazardous Class: B2 FLAMMABLE LIQUIDS
D2A VERY TOXIC
D2B TOXIC EYE AND SKIN IRRITANT

NFPA RATINGS: HEALTH 2; FLAMMABILITY 3; INSTABILITY: 0
HMIS RATINGS: HEALTH 2; FLAMMABILITY 3; INSTABILITY: 0

Target Organs
Bladder, Liver, Kidney, Brain

GHS Classification
Flammable liquids (Category 2)
Skin corrosion/irritation (Category 3)
Serious eye damage/eye irritation (Category 2A)
Specific target organ toxicity - single exposure (Category 3), Central nervous system
Skin irritation (Category 2)
Reproductive toxicity (Category 2)
Specific target organ toxicity - repeated exposure (Category 2)
Aspiration hazard (Category 1)
Acute aquatic toxicity (Category 2)

Signal word: **DANGER**

Hazard Statements
H225 Highly flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.
H401 Toxic to aquatic life.

Precautionary Statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P281 Use personal protective equipment as required.
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P331 Do NOT induce vomiting.

GHS Labeling Pictograms



Section 3- COMPOSITION / INFORMATION ON INGREDIENTS

	Cas No.	Percentage (W/W)	Exposure Guidelines		
			ACGIH TLV	TLV-TWA	OSHA PEL-STEL
Acetone	67-64-1	40-70*	500 ppm	1000 ppm	Not Listed
Toluene	108-88-3	30-60*	20 ppm	200 ppm	300 ppm

**Exact percentages are withheld as a trade secret however the health and environmental hazard effects stated in this SDS describe the effects of the highest concentration of each ingredient; in compliance with (ST/SG/AC.10/30/Rev.6) and (29 CFR 1910.1200).*

Section 4 - FIRST AID MEASURES

Eye Contact: Immediately flush eyes with gently flowing water for at least 15 minutes or until the chemical is removed. Hold eyelids open during flushing. Take care not to rinse the contaminated water into the unaffected eye or face. Seek immediate medical attention.

Skin Contact: Remove contaminated clothing, including shoes, after flushing with water has begun. Flush with copious amounts of water. If irritation persists or signs of toxicity occur, seek medical attention.

Inhalation: Move victim to fresh air. If the affected person is not breathing, apply artificial respiration. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation (CPR) immediately. Obtain medical attention IMMEDIATELY. This material can cause lung damage.

Ingestion: Seek immediate medical attention. Do NOT Induce vomiting. Do

not attempt to give anything by mouth to an unconscious or convulsing person. This material is an aspiration hazard. Can enter lungs and cause damage. If spontaneous vomiting occurs, have victim lean forward with head down to avoid aspirating the liquid into the lungs. Administer artificial respiration if breathing has stopped. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation (CPR) immediately.

Note to Physician: This product contains materials that may cause severe pneumonitis if aspirated. Treatment based on sound judgment of physician and individual reactions of patient.

Section 5 – FIRE FIGHTING MEASURES

Flash Point: -25°C
Flash Point Method: (Tag Closed cup)
Auto Ignition Temp: >465°C
Flammable Limits in air (%): Lower: 1.4% Upper: 12.8%
Extinguishing Media: Use DRY Chemicals. CO2. alcohol foam or water spray. This material may produce a floating fire hazard in extreme fire conditions.

Special Exposure Hazards: Flammable Liquid. May release flammable mixtures when temperatures are at or above the flash point. Toxic gases will form upon combustion. Closed containers may explode when exposed to extreme heat. Isolate and restrict area access. Stop leak only if safe to do so. Move containers from fire area if you can do so without risk. Fight fire from a safe distance and from a protected location. Use fine water spray or fog to control fire spread and cool adjacent structures or containers. This material may produce a floating fire hazard in extreme fire conditions. Vapours are heavier than air and may accumulate in low areas. Vapours may travel a considerable distance along the ground where they can ignite, flashback or explode. May create vapour/air explosion hazard indoors, outdoors and, in sewers. Do not allow runoff to enter waterways or sewer.

Hazardous Decomposition/ Combustion Materials: A Complex mixture of airborne solids, liquids, gases including carbon monoxide, carbon dioxide, and unidentified hydrocarbon fragments will be evolved when this material undergoes combustion.

Special Protective Equipment: Respiratory and eye protection as well as protective clothing required for fire fighting personnel. Full protective equipment and self-contained breathing apparatus (SCBA) should be used in all indoor and any large outdoor fires.

NFPA RATINGS: HEALTH 2; FLAMMABILITY 3; INSTABILITY: 0
HMS RATINGS: HEALTH 2; FLAMMABILITY 3; INSTABILITY: 0

Section 6 – ACCIDENTAL RELEASE MEASURES

Personal Precautionary Measures: Wear appropriate protective equipment.
Environmental Precautionary Measures: Prevent entry into sewers or streams, dike if needed. Consult Local authorities.
Procedure for Clean Up: Flammable liquid. Isolate hazard area and restrict access. Stop

leak only if it is safe to do so. Eliminate all sources of ignition and work only with non-sparking tools. Small Spills: soak up with non-combustible absorbent material and scoop into containers. Large Spills: Prevent contamination of waterways. Dike and pump into suitable containers. Clean up residual with absorbent material. Place in appropriate container. Notify applicable government authority if release is reportable or could adversely affect the environment. Ventilate the area thoroughly.

Section 7 – HANDLING AND STORAGE

Handling:	Flammable. For industrial use only. Handle and open containers with care. Open container slowly to relieve pressure. Avoid contact with eyes, skin and clothing. Do not ingest. Avoid inhalation of chemical. DO NOT handle or store near an open flame, heat, or other sources of ignition. Fixed equipment as well as transfer containers and equipment should be grounded to prevent accumulation of static charge. DO NOT pressurize, cut, heat or weld containers. Empty containers may contain hazardous product residues. Keep the containers closed when not in use. Protect against physical damage. Use appropriate personal protective equipment. Electrostatic charges may be generated during pumping. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge. Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations. Extinguish any naked flames.
Storage:	Store in a cool, dry, well ventilated area, away from heat and ignition sources. Keep containers tightly closed. Store out of direct sunlight and on an impermeable floor.
Empty Containers:	May contain liquid and vapour residue and may be dangerous. "Empty" drums should be completely drained, properly sealed and promptly disposed of in accordance with governmental regulations.

Section 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls:	Local exhaust ventilation is recommended to maintain exposure to within applicable limits (below TLV(s)). Use explosion proof equipment. Make up air should be supplied to balance air that is removed by local or general exhaust ventilation. Ventilate low lying areas such as sumps or pits where dense vapours may collect. Use explosion proof ventilation equipment.
Respiratory Protection:	If exposure exceeds occupational exposure limits, use an appropriate NIOSH approved respirator. In case of spill or leak resulting in unknown concentration, use a NIOSH approved supplied air respirator.
Gloves:	Impervious chemical resistant gloves.
Skin Protection:	Skin contact should be prevented through the use of suitable protective clothing, gloves and footwear, selected for conditions of use and exposure potential. Consideration must be given both to durability as well as permeation resistance.
Eyes:	Chemical goggles; also wear a face shield if splashing hazard exists.
Other Personal Protective Data:	Ensure that eyewash stations and safety showers are proximal to the

work station location.

Ingredients	Exposure Limit	Exposure Limit	PEL-STEL	IDLH *
	ACGIH TLV	OHSA TLV-TWA		
Acetone	500 ppm	1000 ppm	Not Listed	Not Available
Toluene	20 ppm	200 ppm	300 ppm	500 ppm

***Immediately Dangerous to Life and Health**

Section 9 – PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid.
Colour:	Translucent off-white
Odour:	Mild odour
Specific Gravity:	0.86 (water = 1)
Boiling Point:	59 °C
Melting/Freezing Point:	<-7°C
% Volatility:	82% (v/w)
Vapour Pressure:	144 mm Hg. @ 20°C
Vapour Density:	2.3 (Air = 1.0)
Viscosity:	Not Available
VOCs:	520 G/L (4.3 Lbs./Gal. – SCAQMD Rule 1168)
Odour threshold:	Not Available
Solubility:	Not soluble.
Evaporation Rate:	Slower than ethyl ether.

Section 10 – STABILITY AND REACTIVITY

Chemical Stability:	Stable under normal conditions.
Hazardous Polymerization:	Will not occur.
Conditions to Avoid:	High temperatures, sparks, open flames and all sources of ignition.
Materials to Avoid:	Oxidizing agents. Strong bases. Strong alkalis. Reducing agents. Chloroform, nitric compounds, peroxides, sulphur dichloride.
Hazardous decomposition Products:	Under fire conditions, carbon monoxide, carbon dioxide, smoke, fumes, and hydrocarbon fragments can be released.

Section 11 – TOXICOLOGICAL INFORMATION

Chronic: Liver and kidney damage. May cause corneal opacity. May cause central nervous system depression causing headaches, nausea, dizziness and, in extreme cases, convulsions and coma. May cause birth defects.

Principle Routes of Exposure:

Ingestion: May cause severe injury to intestinal tract, liver, kidneys, stomach, throat, lungs, mouth and mucous membranes. Aspiration hazard! Small amounts aspirated into the lungs during ingestion or vomiting may cause lung injury, possibly leading to death. Symptoms of aspiration into the lungs include coughing, gasping, choking, shortness of breath, bluish discoloured skin, rapid breathing and heart rate. Chemical pneumonitis from aspiration may result in fever. Pulmonary edema or bleeding, drowsiness, confusion, coma

and seizures may occur in more serious cases. Symptoms may develop immediately or as late as 24 hours after the exposure, depending on how much chemical entered the lungs.

Skin Contact:

May cause moderate skin irritation. Burning sensation may result. Repeated or prolonged contact may cause defatting and drying of the skin which may result in skin irritation and dermatitis. Skin absorption of material may cause systemic toxicity.

Inhalation:

Respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing and difficulty breathing. If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath and fever. High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.

Eye Contact:

Causes eye irritation. Symptoms of exposure may include: a burning sensation, redness, swelling and blurred vision. May damage eyes.

Material:

Oral LD50: Dermal LD50: Inhalation LC50

Toluene:

636 mg/kg (rat) 12.1 g/kg (rabbit) 400 ppm/24 hr. (mouse)

Acetone:

5,800 mg/kg (rat) 20 g/kg (rabbit) 16,000 ppm (rat)

Carcinogenicity:

IARC – Not Suspected as a human carcinogen.

ACGIH – Toluene is Listed.

OSHA – Not Suspected as a human carcinogen.

NTP – Not Suspected as a human carcinogen.

Carcinogenicity Comment:

This product contains the following chemicals known to the state of California (Proposition 65) to cause cancer or reproductive toxicity: Toluene.

**Reproductive Toxicity/
Terratogenicity/Embryotoxicity/
Mutagenicity:**

Toluene: is fetotoxic in rats and mice at maternally toxic levels.

Significant fetal effects included skeletal anomalies (fused vertebrae and extra ribs) in animals exposed to doses of 1000 mg/m³ toluene for 24 hours/day and retarded skeletal development in animals exposed to 1000 mg/m³ for 8 hours/day. In mice, mean fetal weight was significantly reduced, and the percentage of weight retarded fetuses was significantly increased at the 500 mg/m³ exposure level. Fetotoxic effects in rats occurred at 1500 and 3000 ppm and included decreased litter and mean fetal body weights and decreased sternbrae ossification. Significant fetal effects at 2000 ppm included reduced pup weight, high fetal mortality and embryonic growth retardation. Effects seen in fetuses from pregnant rats administered toluene by gavage included reduced body weight and organ weight producing a generalized growth retardation. In mice exposed to 200 ppm toluene, the incidence of fetuses with dilated renal pelvis was significantly increased, suggesting desynchronization of maturation with respect to development and growth.

Acetone: Studies on 891 women has shown an increased risk of miscarriage.

Section 12 - ECOLOGICAL INFORMATION

Ecotoxicological Information:	Ecotoxicity – Fish Species Data	Acute Crustaceans Toxicity:	Ecotoxicity Freshwater Algae
Toluene:	LC50 (Lepomis macrochirus) 13 mg/L	Not Available	EC50 (Selenastrum capricornutum) 433mg/L
	LC50 (Pimephales promelas) 25 mg/L		
Other Information:	Do not allow product or runoff from fire to enter storm or sanitary sewers, lakes, rivers, streams or public waterways. Block off drains and ditches. Spill areas must be cleaned and restored to original condition or to the satisfactions of authorities. May be harmful to aquatic life. Highly volatile, will partition rapidly to air.		

Section 13 – DISPOSAL CONSIDERATIONS

Disposal of Waste Method:	Disposal of all wastes must be done in accordance with local, state/provincial and federal regulations.
Contaminated Packaging:	Empty containers should be recycled or disposed of through an approved waste management facility.

Section 14 – TRANSPORT INFORMATION

Proper Shipping Name:	ADHESIVES (containing flammable liquid)
Hazard Class:	3
UN Number:	UN 1133
Packing Group:	II
TDG (IATA and IMO):	Cl. 3 UN 1133 PG. II
Hazard Label / Placards:	FLAMMABLE

Section 15 – REGULATORY INFORMATION

U.S. TSCA Inventory Status: All compounds of this product are either on the Toxic Substances Control Act (TSCA) Inventory List or exempt.

Canadian DSL Inventory Status: All compounds of this product are either on the Domestic Substances List (DSL); the Non- Domestic Substances List (NDSL) or exempt.

Note: Not available.

US Regulatory Rules

	CECLA/SARA Section 302:	SARA (311, 312) Hazard Class:	CERCLA/SARA Section 313:
Components of STR-PVC:	Not Listed	Listed	Listed
California Proposition 65:	Listed.		

MA Right to Know List: Listed.
New Jersey Right-to-know List: Listed.
Pennsylvania Right to Know List: Listed.

WHMIS Hazardous Class: B2 FLAMMABLE LIQUIDS
D2A VERY TOXIC
D2B TOXIC EYE AND SKIN IRRITANT

NFPA RATINGS: HEALTH 2; FLAMMABILITY 3; INSTABILITY: 0
HMIS RATINGS: HEALTH 2; FLAMMABILITY 3; INSTABILITY: 0

Section 16 – OTHER INFORMATION

All employees or contractors etc. who use this product must have access to this Safety Data Sheet.

This information is furnished without warranty, representation, inducement or licence of any kind, except that it is accurate to the best of IMTECH Rubber Products knowledge or is obtained from sources believed by IMTECH Rubber Products to be accurate. IMTECH Rubber Products makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use or reliance on same. Customers are encouraged to conduct their own tests.

DATE OF ISSUE: Oct. 27, 2015
HISTORY REVISION: SDS updated to comply with GHS regulations.
Replaces MSDS dated Dec 01, 2014.
PREPARED BY: IMTECH Rubber Products

END OF SDS